



**MOD. KV-1500-EL STANDARD****230 V****MOD. KV-1500-EL SPECIAL****400 V**

Technical Data	
<b>Power</b>	1,5 KW / 50/60 HZ
<b>Voltage</b>	230 / 400 V 1~
<b>Max. Amp drawing</b>	9,5 Ampere
<b>Motor protection</b>	IP55
<b>Max. airflow</b>	230m3/h
<b>Max. water lift</b>	2750 mm. H20
<b>Max. water lift on continuous duty</b>	1900 mm. H20
<b>Filter type</b>	1 cartridge
<b>Filter surface</b>	30.000 cm2
<b>Filter efficiency</b>	class M / 1 micron
<b>Filter cleaning type</b>	manual
<b>Collection container capacity</b>	35 liters
<b>Noise level</b>	70 dB
<b>Pressure relief valve</b>	installed

**MOD. KV-3000-EL**

Technical Data	
<b>Power</b>	2,2 KW / 50/60 HZ
<b>Voltage</b>	400 V 3~
<b>Motor protection</b>	IP55
<b>Max. airflow</b>	300 m3/h
<b>Max. water lift</b>	3000 mm. H20
<b>Max. water lift on continuous duty</b>	2300 mm. H20
<b>Filter type</b>	1 cartridge
<b>Filter surface</b>	30.000 cm2
<b>Filter efficiency</b>	class M / 1 micron
<b>Filter cleaning type</b>	manual
<b>Collection container capacity</b>	35 liters
<b>Noise level</b>	73 dB
<b>Pressure relief valve</b>	installed

**MOD. KV-5500-EL**

Technical Data	
<b>Power</b>	2,2 KW / 50/60 HZ
<b>Voltage</b>	400 V 3~
<b>Motor protection</b>	IP55
<b>Max. airflow</b>	550 m3/h
<b>Max. water lift</b>	3000 mm. H20
<b>Max. water lift on continuous duty</b>	2200 mm. H20
<b>Filter type</b>	2 cartridges
<b>Filter surface</b>	56.000 cm2
<b>Filter efficiency</b>	class M / 1 micron
<b>Filter cleaning type</b>	automatic - reverse pulse compressed air cleaning
<b>Collection container capacity</b>	100 liters
<b>Noise level</b>	75 dB
<b>Compressor</b>	installed
<b>Pressure relief valve</b>	installed

AIRTEC AG / SA / LTD

Industriestrasse 40, CH-4455 Zunzgen / Baselland, Schweiz

Tel.: +41(0) 61 976 95 25, Fax: +41(0) 61 976 95 26

E-Mail: info@airtec.com, Internet: www.airtec.com


**ISO 9001**  
**BUREAU VERITAS**  
 Certification
